

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MARISEAL 600 Component B**

Safety data sheet no.: XXP016880-b

1.2 Relevant identified uses of the substance or mixture and uses advised against

The product is intended for industrial or professional use.

Application of the substance / the mixture Coating material

Uses advised against Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Manufacturer/Supplier:

MARIS POLYMERS S.M.S.A.

Industrial Area of Inofita, 32 011 Inofita, Greece

Tel. : +30 22620 32918-9

e-mail: marispolymers@saint-gobain.com

Distributor:

Saint-Gobain Construction Products Polska Sp. z o.o.

ul. Okrężna 16, 44-100 Gliwice

Phone: +48 41 35 69 317 (Mon-Fri 9.00-16.00)

e-mail: SDS.pl@saint-gobain.com

1.4 Emergency telephone number:

112 (emergency number), 999 (ambulance), 998 (fire department).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

(Contd. on page 2)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 1)

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

reaction mass of ethylbenzene and m-xylene and p-xylene
m-tolylidene diisocyanate

Hazard statements

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P331 Do NOT induce vomiting.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with non hazardous additions.

(Contd. on page 3)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 2)

Dangerous components:

EC number: 905-562-9 Reg.nr.: 01-2119488216-32-xxxx	reaction mass of ethylbenzene and m-xylene and p-xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limit: STOT RE 2; H373: C ≥ 10%	≥10-<15%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34-xxxx	m-tolylidene diisocyanate ⚠ Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	≥0.1-<0.5%

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

Seek immediate medical advice

After inhalation

Supply fresh air and to be sure call for a doctor.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

Seek medical treatment in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

Seek immediate medical advice.

After swallowing

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

EUG

(Contd. on page 4)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 3)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents CO₂, powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Wear fully protective suit.

Mouth respiratory protective device.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb with sawdust or other combustible absorbents.

Dispose of contaminated material as waste according to point 13.

Absorb liquid components with liquid-binding material.

Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Handle with care. Avoid jolting, friction and impact.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Flammable gas-air mixtures may form in empty receptacles.

Protect from heat.

(Contd. on page 5)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 4)

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store in cool, dry conditions in well sealed receptacles.

Store under lock and key and with access restricted to technical experts or their assistants only.

Store receptacle in a well ventilated area.

Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs

reaction mass of ethylbenzene and m-xylene and p-xylene

Oral	Derived No Effect Level	12.5 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	212 mg/kgxday (worker systemic long term value) 125 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	221 mg/m ³ (worker systemic long term value) 442 mg/m ³ (worker systemic short term value) 65.3 mg/m ³ (consumer systemic long term value) 260 mg/m ³ (consumer systemic short term value)

CAS: 26471-62-5 m-tolyldiene diisocyanate

Inhalative	Derived No Effect Level	0.035 mg/m ³ (worker systemic long term value) 0.14 mg/m ³ (worker systemic short term value) 0.14 mg/m ³ (worker local short term value) 0.035 mg/m ³ (worker local long term value)
------------	-------------------------	--

PNECs

reaction mass of ethylbenzene and m-xylene and p-xylene

Predicted No-Effect Concentration	0.327 mg/l (sea water rating factor) 0.327 mg/l (fresh water rating factor)
-----------------------------------	--

CAS No. / Designation of material / % / Type / Value / Unit

CAS: 26471-62-5 m-tolyldiene diisocyanate

MAK (Germany)	vgl. Abschn.XII
OEL (Sweden)	Short-term value: 0.04 mg/m ³ , 0.005 ppm Long-term value: 0.014 mg/m ³ , 0.002 ppm C, M, S

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 5)

HTP (Finland)	Short-term value: 0.035 mg/m ³ NCO
---------------	--

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A2/P2.

Hand protection

Protective gloves against chemicals (standard EN 374-1)

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Due to missing tests no recommendation to the glove material can be given for the product/ the mixture/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommendation: contaminated gloves should be disposed of.

Butyl rubber, BR

Fluorocarbon rubber (FKM-Viton)

Recommended thickness of the material: ≥ 0.5 (BR); 0.4 (Viton) mm

Penetration time of glove material

The determined breakthrough times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the breakthrough time, is recommended.

For the mixture of chemicals mentioned below the breakthrough time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

Eye/face protection Tightly sealed goggles

Body protection: Protective work clothing.

EUG

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 6)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	137 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	1.1 Vol % Not determined.
Upper:	7 Vol %
Flash point:	30 °C
Ignition temperature:	488 °C (xylene)
Decomposition temperature:	Not determined.
pH	Not applicable.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic at 20 °C:	>90 mPas
Solubility	
Water:	Fully miscible
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	1.02 g/cm ³
Relative density	Not determined.
Bulk density:	Not applicable.
Vapour density	Not determined.

9.2 Other information

Appearance:	No further relevant information available.
Form:	Viscous
Important information on protection of health and environment, and on safety.	
Auto-ignition temperature:	Product is not self-igniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Minimum ignition energy	
Solvent separation test:	Not determined
EU-VOC (g/L)	170.0000 g/l
Change in condition	
Softening point/range	
Oxidising properties	Not determined.
Evaporation rate	Not determined.

(Contd. on page 8)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 7)

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids Flammable liquid and vapour.	
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity Not reactive under normal conditions of use

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

To avoid thermal decomposition do not overheat.

Stable at environment temperature.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid Avoid heat, sparkles, naked flame or other sources of ignition.

10.5 Incompatible materials: Oxydising agents.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
Dermal	LD50	9,964 mg/kg (Calculation)	
Inhalative	LC50/4 h	5.79 mg/l (Calculation)	

reaction mass of ethylbenzene and m-xylene and p-xylene

Oral	LD50	>3,523 mg/kg (Rat)
------	------	--------------------

(Contd. on page 9)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 8)

Dermal	LD50	>12,126 mg/kg (Rabbit)
Inhalative	LC50/4 h	>27 mg/l (Rat)
CAS: 26471-62-5 m-tolylidene diisocyanate		
Oral	LD50	>4,130 mg/kg (Rat)
Dermal	LD50	>9,400 mg/kg (Rabbit)
Inhalative	LC50/4 h	0.1 mg/l (Rat)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test / Effective concentration / Method / Assessment

reaction mass of ethylbenzene and m-xylene and p-xylene

LC50/96h	>2.6 mg/l (Fish)
EC50/24h	96 mg/l (Activated sludge)
EC50/72h	4.6-4.9 mg/l (Algae)
NOEC (21d)	1.57 mg/l (Daphnia magna)

CAS: 26471-62-5 m-tolylidene diisocyanate

LC50/96h	133 mg/l (Fish)
EC50/48h	12.5-18.3 mg/l (Daphnia magna)
EC50/96h	3.2-4.3 mg/l (Algae)

12.2 Persistence and degradability No further relevant information available.

Behaviour in environmental systems:

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene

DT50-value (Degradation Half Time) | 2 day

(Contd. on page 10)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 9)

12.3 Bioaccumulative potential

CAS: 26471-62-5 m-tolyldene diisocyanate

EBAB | 3.43 log Pow (Bioaccumulation)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: Avoid transfer into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Dispose of the product in accordance with national and local regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

European waste catalogue

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA

UN1866

14.2 UN proper shipping name

ADR

1866 RESIN SOLUTION

IMDG, IATA

RESIN SOLUTION

14.3 Transport hazard class(es)

ADR



Class

3 (F2) Flammable liquids.

(Contd. on page 11)

Safety Data Sheet
according to 1907/2006/EC, Article 31


Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 10)

Label	3
IMDG, IATA	
	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S</u> -E
Stowage Category	A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
Remarks:	Containers >450 L = UN 1866 - 3(F1) - RESIN SOLUTION, flammable
IMDG	
Limited quantities (LQ)	0
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Remarks:	Containers >30 L = UN 1866 - 3(F1) - RESIN SOLUTION, flammable
IATA	
Remarks:	Outside ADR/IMDG = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable
UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

(Contd. on page 12)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 11)

Regulation (EC) No 1272/2008 (CLP)
Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)
Directive 2004/42/CE (VOC), cf. section 9

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations

Other regulations, limitations and prohibitive regulations

BG-Merkblätter: M 044 "Polyurethane production/Isocyanates"

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.

(Contd. on page 13)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 22.11.2021

Trade name MARISEAL 600_Component B

(Contd. of page 12)

H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
EUH204 Contains isocyanates. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Bridging principles
Acute toxicity - inhalation Aspiration hazard	Expert judgement
Skin corrosion/irritation Serious eye damage/irritation Respiratory sensitisation Specific target organ toxicity (repeated exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: SUSTCHEM S.A

Contact:

SUSTCHEM S.A.
REACH & Chemical Services Department
A: 144, 3rd Septemvriou, GR 112 51 | Athens, Greece
T: +30 210 8252510 | F: +30 210 8252575
W: www.sustchem.gr | E: info@suschem.gr

Date of previous version: 28.07.2021

Version number of previous version: 5

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern (REACH regulation)
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.