

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name **MARISEAL KATALYSATOR**

Safety data sheet no.: XXP016847

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

The product is intended for industrial or professional use.

**Application of the substance / the mixture** Construction chemicals

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:**

Manufacturer/Supplier:

MARIS POLYMERS S.M.S.A.

Industrial Area of Inofita, 32 011 Inofita, Greece

Tel. : +30 22620 32918-9

e-mail: marispolymers@saint-gobain.com

**Distributor:**

Saint-Gobain Construction Products Polska Sp. z o.o.

ul. Okrężna 16, 44-100 Gliwice

Phone: +48 41 35 69 317 (Mon-Fri 9.00-16.00)

e-mail: SDS.pl@saint-gobain.com

**1.4 Emergency telephone number:**

112 (emergency number), 999 (ambulance), 998 (fire department).

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2

H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1

H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4

H312 Harmful in contact with skin.

Acute Tox. 4

H332 Harmful if inhaled.

(Contd. on page 2)

EUG

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 1)

Skin Irrit. 2            H315 Causes skin irritation.  
Eye Irrit. 2            H319 Causes serious eye irritation.  
STOT SE 3            H335 May cause respiratory irritation.

**2.2 Label elements**

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**



GHS02   GHS07   GHS08   GHS09

**Signal word** Danger

**Hazard-determining components of labelling:**

reaction mass of ethylbenzene and m-xylene and p-xylene  
diethylmethylbenzenediamine

**Hazard statements**

H226            Flammable liquid and vapour.  
H312+H332    Harmful in contact with skin or if inhaled.  
H315            Causes skin irritation.  
H319            Causes serious eye irritation.  
H335            May cause respiratory irritation.  
H373            May cause damage to organs through prolonged or repeated exposure.  
H304            May be fatal if swallowed and enters airways.  
H411            Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210            Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260            Do not breathe dust/fume/gas/mist/vapours/spray.  
P273            Avoid release to the environment.  
P280            Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310    IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P501            Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Description:** Mixture consisting of the following components.

(Contd. on page 3)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 2)

**Dangerous components:**

EC number: 905-562-9 Reg.nr.: 01-2119488216-32-xxxx	reaction mass of ethylbenzene and m-xylene and p-xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limit: STOT RE 2; H373: C ≥ 10 %	>50-<90%
CAS: 68479-98-1 EINECS: 270-877-4 Index number: 612-130-00-0 Reg.nr.: 01-2119486805-25-xxxx	diethylmethylbenzenediamine ⚠ STOT RE 2, H373; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2, H319	≥10-<25%

**SVHC** Void

**Additional information** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information**

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

Seek immediate medical advice

**After inhalation**

Supply fresh air and to be sure call for a doctor.

Seek medical treatment in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact**

Rinse opened eye for several minutes under running water. Rinse liquid should be tempered (20-30°C).

Protect unharmed eye.

Seek immediate medical advice.

**After swallowing**

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing agents** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray.

(Contd. on page 4)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 3)

**For safety reasons unsuitable extinguishing agents** Water with full jet

**5.2 Special hazards arising from the substance or mixture**

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

**Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

**Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

Avoid inhalation of vapors.

Keep away from ignition sources

Ensure adequate ventilation.

**6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

**6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb with sawdust or other combustible absorbents.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage**

**Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Prevent any seepage into the ground.

Provide ventilation for receptacles.

**Information about storage in one common storage facility:** Store away from foodstuffs.

**Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

(Contd. on page 5)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

**7.3 Specific end use(s)** No further relevant information available.

(Contd. of page 4)

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

<b>DNELs</b>		
<b>reaction mass of ethylbenzene and m-xylene and p-xylene</b>		
Oral	Derived No Effect Level	12.5 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	212 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	125 mg/kgxday (consumer systemic long term value)
		221 mg/m <sup>3</sup> (worker systemic long term value)
		442 mg/m <sup>3</sup> (worker systemic short term value)
		65.3 mg/m <sup>3</sup> (consumer systemic long term value)
		260 mg/m <sup>3</sup> (consumer systemic short term value)
<b>CAS: 68479-98-1 diethylmethylenediamine</b>		
Dermal	Derived No Effect Level	1 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	1 mg/kgxday (consumer systemic long term value)
		0.13 mg/m <sup>3</sup> (worker systemic long term value)
		0.1 mg/m <sup>3</sup> (consumer systemic long term value)
<b>PNECs</b>		
<b>reaction mass of ethylbenzene and m-xylene and p-xylene</b>		
Predicted No-Effect Concentration		0.327 mg/l (sea water rating factor)
		0.327 mg/l (fresh water rating factor)

**8.2 Exposure controls**

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

**Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Respiratory protection required in insufficiently ventilated working areas and during spraying.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Combination of charcoal filter and particulate filter A2-P2 (EN 529)

**Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Protective gloves against chemicals (standard EN 374-1)

(Contd. on page 6)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the mixture/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

Fluorocarbon rubber (FKM-Viton)

Recommended thickness of the material:  $\geq 0.5$  (BR); 0.4 (Viton) mm

Recommendation: contaminated gloves should be disposed of.

**Penetration time of glove material**

The determined breakthrough times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the breakthrough time, is recommended.

For the mixture of chemicals mentioned below the breakthrough time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

**Eye/face protection**

Tightly sealed goggles

Protective eyewear (standard EN 166)

**Body protection:**

Chemically resistant protective work clothing (EN 14605)

Boots

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

<b>Colour:</b>	According to product specification
<b>Odour:</b>	Uncharacteristic.
<b>Odour threshold:</b>	Not determined.
<b>Melting point/freezing point:</b>	Undetermined.
<b>Boiling point or initial boiling point and boiling range</b>	Undetermined.
<b>Flammability</b>	Not applicable.
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Flash point:</b>	27-32 °C (xylene, EC No. 905-562-9 )
<b>Ignition temperature:</b>	480 °C (xylene)
<b>Decomposition temperature:</b>	Not determined.
<b>pH</b>	Not applicable.
<b>Viscosity:</b>	
<b>Kinematic viscosity</b>	Not determined.
<b>dynamic:</b>	Not determined.
<b>Solubility</b>	
<b>Water:</b>	Not miscible or difficult to mix

(Contd. on page 7)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 6)

<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure:</b>	Not determined.
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	0.91 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Bulk density:</b>	Not applicable.
<b>Vapour density</b>	Not determined.

<b>9.2 Other information</b>	No further relevant information available.
<b>Appearance:</b>	
<b>Form:</b>	Liquid
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Auto-ignition temperature:</b>	Product is not self-igniting.
<b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Minimum ignition energy</b>	
<b>Solvent separation test:</b>	Not determined
<b>EU-VOC (g/L)</b>	<680.0000 g/l
<b>Change in condition</b>	
<b>Softening point/range</b>	
<b>Oxidising properties</b>	Not considered as oxidising.
<b>Evaporation rate</b>	Not determined.

**Information with regard to physical hazard**

<b>classes</b>	
<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	
Flammable liquid and vapour.	
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

**SECTION 10: Stability and reactivity**

**10.1 Reactivity** No further relevant information available.

(Contd. on page 8)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 7)

**10.2 Chemical stability**

**Thermal decomposition / Conditions to be avoided:** Stable at environment temperature.

**10.3 Possibility of hazardous reactions** No dangerous reactions known

**10.4 Conditions to avoid** Avoid heat, sparkles, naked flame or other sources of ignition.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Harmful in contact with skin or if inhaled.

**LD/LC50 values relevant for classification:**

Components	Type	Value	Species
Oral	LD50	2,954 mg/kg	(Rat)
Dermal	LD50	1,101 mg/kg	(Calculation)
Inhalative	LC50/4 h	14.7 mg/l	(Calculation)

**reaction mass of ethylbenzene and m-xylene and p-xylene**

Oral	LD50	>3,523 mg/kg	(Rat)
Dermal	LD50	>12,126 mg/kg	(Rabbit)
Inhalative	LC50/4 h	>27 mg/l	(Rat)

**CAS: 68479-98-1 diethylmethylbenzenediamine**

Oral	LD50	738 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation** Causes serious eye irritation.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

None of the ingredients is listed.

EUG

(Contd. on page 9)



**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 8)

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:** Toxic to aquatic life with long lasting effects.

**Type of test / Effective concentration / Method / Assessment**

**reaction mass of ethylbenzene and m-xylene and p-xylene**

LC50/96h	>2.6 mg/l (Fish)
EC50/24h	96 mg/l (Activated sludge)
EC50/72h	4.6-4.9 mg/l (Algae)
NOEC (21d)	1.57 mg/l (Daphnia magna)

**CAS: 68479-98-1 diethylmethylenediamine**

LC50/48h	200 mg/l (Fish)
EC50/48h	0.5 mg/l (Daphnia magna)

**12.2 Persistence and degradability** No further relevant information available.

**Behaviour in environmental systems:**

**Components:**

**reaction mass of ethylbenzene and m-xylene and p-xylene**

DT50-value (Degradation Half Time)	2 day
------------------------------------	-------

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects**

**Remark:** Toxic for fish

**Additional ecological information:**

**General notes:**

Do not allow product to reach ground water, water course or sewage system.

The product contains materials that are harmful to the environment.

Also poisonous for fish and plankton in water bodies.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Recommendation**

Dispose of the product in accordance with national and local regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 10)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 9)

HP6	Acute Toxicity
HP14	Ecotoxic

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

**14.1 UN number or ID number**  
ADR, IMDG, IATA

UN1866

**14.2 UN proper shipping name**  
ADR

1866 RESIN SOLUTION, ENVIRONMENTALLY  
HAZARDOUS  
IMDG  
RESIN SOLUTION, MARINE POLLUTANT  
IATA  
RESIN SOLUTION

**14.3 Transport hazard class(es)**

ADR



**Class**  
**Label**

3 (F1) Flammable liquids.  
3

IMDG



**Class**  
**Label**

3 Flammable liquids.  
3

IATA



**Class**  
**Label**

3 Flammable liquids.  
3

**14.4 Packing group**  
ADR, IMDG, IATA

III

**14.5 Environmental hazards:**

Product contains environmentally hazardous  
substances: Diethyltoluenediamine  
Marine pollutant: Symbol (fish and tree)  
Special marking (ADR): Symbol (fish and tree)

(Contd. on page 11)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 10)

<b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
<b>Hazard identification number (Kemler code):</b>	30
<b>EMS Number:</b>	F-E, S-E
<b>Stowage Category</b>	A

<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
---	-----------------

**Transport/Additional information:**

**ADR**

<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>Transport category</b>	3
<b>Tunnel restriction code</b>	D/E

**IMDG**

<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

<b>UN "Model Regulation":</b>	UN 1866 RESIN SOLUTION, 3, III, ENVIRONMENTALLY HAZARDOUS
-------------------------------	---

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)  
Regulation (EC) No 1272/2008 (CLP)  
Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)  
Directive 2004/42/CE (VOC), cf. section 9  
**Labelling according to Regulation (EC) No 1272/2008** cf. section 2

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category**

E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 12)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 11)

**REGULATION (EU) 2019/1148**

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

**Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

**Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	Bridging principles
Acute toxicity - dermal Acute toxicity - inhalation Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
Aspiration hazard	Expert judgement

**Department issuing SDS:** SUSTCHEM S.A

**Contact:**

SUSTCHEM S.A.  
REACH & Chemical Services Department

(Contd. on page 13)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 3 (replaces version 2)

Revision: 29.11.2021

**Trade name MARISEAL KATALYSATOR**

(Contd. of page 12)

A: 144, 3rd Septemvriou, GR 112 51 | Athens, Greece

T: +30 210 8252510 | F: +30 210 8252575

W: www.sustchem.gr | E: info@suschem.gr

**Date of previous version: 10.02.2021**

**Version number of previous version: 2**

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**\* Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.